

Rohs

| REV. | DESCRIPTION | DRAW. | DATE. |
|------|-------------|-------|-------|
| | | | |
| | | | |

| No:of pins | Dimension | | |
|------------|-----------|-------|-------|
| | DIM.A | DIM.B | DIM.C |
| 03 | 5.00 | 9.00 | 11.95 |
| 04 | 7.50 | 11.50 | 14.45 |
| 05 | 10.00 | 14.00 | 16.95 |
| 06 | 12.50 | 16.50 | 19.45 |
| 07 | 15.00 | 19.00 | 21.96 |
| 08 | 17.50 | 21.50 | 24.45 |
| 09 | 20.00 | 24.00 | 26.95 |
| 10 | 22.50 | 26.50 | 29.45 |
| 11 | 25.00 | 29.00 | 31.95 |
| 12 | 27.50 | 31.50 | 34.45 |

Material:
Insulator : NYLON 9T (UL94V-0)
Contact : Phosphor Bronze
Contact Plated : Gold over Nickel or Tin
Specification:
Current Rating : 5A
Instant Current : 7A
Voltage Rating : 30V
Contact Resistance : 30m Ω
Insulation Resistance : 100M Ω
Dielectric Voltage : 500V
Operating Temperature : -25°~85°

AUGO

AUGO ELECTRONICS CO.,LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

REV:

01

SIZE:

A4

SCALE: 1:1

UNIT: mm

SHEET: 1/1



UNLESS OTHERWISE
SPECIFIED,TOLERANCE:

X. ±0.20

X.x ±0.15

X.xx ±0.10

ANGULAR ±2°

TITLE:

BATTERY FEMALE 2.5 PITCH
BOARD TO BOARD CONNECTOR

PART NO:

AUGO-B10F-A-3.4

DESIGN

G.C.CHEN

DATE

DRAWING

Y.C.ZHANG

DATE

CHECK

D.J.WANG

DATE

SCALE

1:1

PAGE

1 OF 1